

DETAILS

WIDTH: 18" / 24" / 30"

Determined by package size, available conveying area and application specific needs

LENGTH EXTENDED: 20' - 68'

Determine total length needed, including curvatures and obstructions

AXLE CENTER: 3" / 4" / 5.25"

Package size determines necessary axle center length on fully extended conveyor

SKATE WHEEL TYPE: STEEL / BLACK / RED

Determined by package weight, durability, operational flow control, and application specific needs

The NestaFlex® 376 PL is the leading expandable, gravity conveyor for outbound shipments and can be equipped with several engineered options to enhance productivity. With the fixed height legs, the conveyor maintains the required pitch to provide gravity flow. The leg brackets are engineered to keep the legs perpendicular to the floor when it is fully extended and contracted for maximum performance of the swivel casters.

The NestaFlex® 376 PL truck loader systems include a guide track and a herringbone transition that assists in extending and contracting the NestaFlex® under your fixed conveyor. This system provides a smooth transition of packages between the fixed conveyor and the NestaFlex® 376 PL conveyor. Its all steel construction gives you the highest quality flexible gravity conveyor for fluid loading of trailers at your docks.





NESTAFLEX 376 PL GRAVITY SKATE WHEEL CONVEYOR

SPECIFICATIONS

18" WIDE MODELS		24" WIDE MODELS		30" WIDE MODELS		LENGTH ADJUSTMENTS	
MODEL#	LEG SETS	MODEL#	LEG SETS	MODEL#	LEG SETS	CONTRACTED	EXTENDED
37618052	14	37624052	14	37630052	14	13′ 3″	47′ 0″
37618064	17	37624064	17	37630064	17	16′ 1″	58′ 10″

All conveyor products can be modified to suit specific design requirements Please contact our sales representatives for details on sizes or options that are not listed.

STANDARD FEATURES

- •Load capacity 376 lbs/ft
- Steel skate wheels with steel ball bearings
- •3" axle centers for first 10' of conveyor; remaining footage is 5.25" axle centers
- Elevations preset based on application
- Heavy duty steel square tubing
- •Zinc plated legs
- Perpendicular legs
- •Welded double horizontal leg braces
- •Longitudinal leg brace on infeed & discharge
- \bullet Heavy duty 6" x 2" casters with 4 total lock brake casters only on discharge end
- •7 gauge steel side links assembled using shoulder bolts with Loctite and steel locking nuts
- •5/16" Ø axle across the width
- •Self-tracking design
- Heavy duty roller package stop

OPTIONS

- •4" and 3" axle centers
- •Black poly skate wheels with steel ball bearings
- •8" x 2" casters
- •36" conveyor width

ACCESSORIES

- Curve Guards
- Rigid Discharge Cart
- Herringbone transition
- Guide Track
- Power Assist
- •T-Junction
- Heavy Duty Impact Cart

TECHNICAL DATA

CONSTRUCTION

All Steel Bolted Construction

LEGS

Zinc Plated, heavy-duty leg supports 1.25" square steel tubing with a double welded cross brace

SIDE LINKS

Made of 7 gauge steel with Loctite shoulder bolts and steel locking nuts

WARRANTY

MECHANICAL: 24 Months


SERVICES AVAILABLE

Technical Support Installation & Setup Service Maintenance Application Support Hardware Support

OPTIMAL PACKAGE SIZE FOR AXLE CENTERS				
AXLE CENTER LENGTH	PACKAGE SIZES			
5.25"	15" & LARGER			
4"	12" & LARGER			
3"	9" & LARGER			



STEEL SKATE WHEELS WITH STEEL BALL BEARINGS



BLACK POLY SKATE WHEELS WITH STEEL BALL BEARINGS

800.327.9209 | FMHSALES@FMHCONVEYORS.COM | WWW.FMHCONVEYORS.COM



FMH CONVEYORS IS A MEMBER OF THE **DURAVANT** FAMILY OF COMPANIES

PACKAGING SOLUTIONS | FOOD PROCESSING SOLUTIONS | MATERIAL HANDLING SOLUTIONS | SUPPORTPRO

www.duravant.com



DETAILS

WIDTH: 18" / 24" / 30"

Determined by package size, available conveying area and application specific needs

LENGTH EXTENDED: 8' - 60'

Determine total length needed, including curvatures and obstructions

AXLE CENTER: 3" / 4" / 5.25"

Package size determines necessary axle center length on fully extended conveyor

SKATE WHEEL TYPE: STEEL / BLACK / RED

Determined by package weight, durability, operational flow control, and application specific needs

The NestaFlex® 376 AL/FL is a heavy duty, gravity conveyor that features double welded cross braces and heavy duty square tubing legs available in adjustable height legs (AL) and fixed height legs (FL). This all bolted design uses shoulder bolts, steel lock nuts and is additionally secured with industrial thread lock to help reduce maintenance. The four point leg connection gives additional strength to the conveyor to make it last longer. The NestaFlex® 376 AL/FL is designed to provide the support necessary to handle heavy packages in high volume environments.

The **NestaFlex® 376 AL/FL** has a proven track record in the industry and is the choice for medium to high volume shipping and receiving departments in distribution centers, retail stores, and manufacturing and assembly operations.





SPECIFICATIONS

18" WIDE MODELS		24" WIDE MODELS		30" WIDE MODELS		LENGTH ADJUSTMENTS	
MODEL#	LEG SETS	MODEL#	LEG SETS	MODEL#	LEG SETS	CONTRACTED	EXTENDED
37618008	3	37624008	3	37630008	3	2′ 7″	8′ 6″
37618012	4	37624012	4	37630012	4	3′ 7″	12′ 2″
37618016	5	37624016	5	37630016	5	4′ 8″	15′ 10″
37618020	6	37624020	6	37630020	6	5′ 8″	19′ 6″
37618024	7	37624024	7	37630024	7	6′ 8″	23′ 2″
37618028	8	37624028	8	37630028	8	8′ 2″	28′ 0″
37618032	9	37624032	9	37630032	9	9′ 2″	31′ 8″
37618036	10	37624036	10	37630036	10	10′ 3″	35′ 4″
37618040	12	37624040	12	37630040	12	12′ 1″	41′ 10″
37618044	13	37624044	13	37630044	13	13′ 1″	45′ 6″
37618048	14	37624048	14	37630048	14	14′ 4″	49′ 5″
37618052	15	37624052	15	37630052	15	15′ 4″	53′ 1″
37618056	16	37624056	16	37630056	16	16′ 5″	56′ 9″
37618060	17	37624060	17	37630060	17	17′ 5″	60′ 5″

All conveyor products can be modified to suit specific design requirements Please contact our sales representatives for details on sizes or options that are not listed.

STANDARD FEATURES

- •Load capacity 376 lbs/ft
- Steel skate wheels with steel ball bearings
- •5.25" axle centers
- •28" 36" adjustable conveyor heights (AL ONLY) using hand knobs to raise or lower the legs for 5" casters; 29"–37" for 6" casters
- Fixed leg (FL ONLY) height adjustments determined per application and are preset by set screws or hand knob
- Heavy duty steel square tubing zinc plated legs
- •Welded double horizontal leg braces
- Heavy duty 5" x 1.5" casters with 2 total lock brake casters on each end (all conveyors up to 40' in length); 6" x 2" (all conveyors over 40' in length)
- •5/16" Ø axle across the width
- Self-tracking design
- Couplers easily connect two or more conveyors
- Heavy duty retractable package stop

OPTIMAL PACKAGE SIZE FOR AXLE CENTERS				
AXLE CENTER LENGTH	PACKAGE SIZES			
5.25"	15" & LARGER			
4"	12" & LARGER			
3"	9" & LARGER			

OPTIONS

- •4" and 3" axle centers
- Additional brake casters
- Additional set of couplers
- $\bullet AL$ ONLY leg height adjustments:
- •5" casters: 20"-26"; 24"-32"; 26"-44"; 44"-52"
- •6" casters: 21"-27"; 25"-33"; 37"-45"; 45"-53"
- Black poly wheels w/ steel ball bearings
- Red poly wheels w/ nylon bushings
- •Caster upgrades 6" or 8"
- Outboard couplers
- •36" conveyor width

ACCESSORIES

- Curve Guards
- •Side Handles
- Swing Stick
- Heavy Duty Impact Cart
- •T-Junction

TECHNICAL DATA

CONSTRUCTION

All Steel Bolted Construction

LEGS

Zinc Plated, heavy-duty leg supports 1.25" square steel tubing with a double welded cross brace

SIDE LINKS

Made of 7 gauge steel with Loctite shoulder bolts and steel locking nuts

WARRANTY

MECHANICAL: 24 Months

SERVICES AVAILABLE

Technical Support Installation & Setup Service Maintenance Application Support Hardware Support



STEEL SKATE WHEELS WITH STEEL BALL BEARINGS



BLACK POLY SKATE WHEELS WITH STEEL BALL BEARINGS



RED POLY SKATE WHEELS WITH NYLON BUSHINGS

800.327.9209 | FMHSALES@FMHCONVEYORS.COM | **WWW.FMHCONVEYORS.COM**



FMH CONVEYORS IS A MEMBER OF THE **DURAVANT** FAMILY OF COMPANIES

PACKAGING SOLUTIONS | FOOD PROCESSING SOLUTIONS | MATERIAL HANDLING SOLUTIONS | SUPPORTPRO

www.duravant.com